

升降式高温炉 Elevator High Temperature Furnace



加热方式	<ul style="list-style-type: none"> ☑ 电加热 (热风循环) ☑ 燃气加热 ☑ 石墨加热
功能叙述与优点	<ul style="list-style-type: none"> ☑ 均温度优良 ($\pm 5^{\circ}\text{C}$) ☑ 在加热室能自动控温和显示氧含量 ☑ 可依客户需求, 提供炉内不同的充入气体和环境 ☑ 特殊保温节省能源消耗 ☑ 提供高纯度的气体环境, 并减少气体消耗
使用于	<ul style="list-style-type: none"> ☑ 还原 ☑ 段烧/焙烧 ☑ 烧结 ☑ 涂料

型号	尺寸(mm) (W×L×H)	温度范围 ($^{\circ}\text{C}$)
EF-01	500×500×500	100~1200
EF-02	800×800×800	100~1200
EF-03	1000×1000×1000	100~1200
EF-04	1500×1500×1500	100~1200
EF-05	2000×2000×2000	100~1200
EF-C	依照需求客制化尺寸	100~1200

升降式高温炉 Elevator High Temperature Furnace



Heating Method	<ul style="list-style-type: none"> ☞ Electric Heating (convection) ☞ Gas Heating ☞ Graphite Heating (in higher temperature)
Description & Advantage	<ul style="list-style-type: none"> ☞ Temperature Uniformity ($\pm 5^{\circ}\text{C}$) ☞ Automatic temperature control and oxygen content in the chamber ☞ Accommodate reactive or inert gas atmospheres upon customer's request ☞ Energy efficient design insulation ☞ Ultra-pure atmospheric environment with minimal gas consumption
Application	<ul style="list-style-type: none"> ☞ Reduction ☞ Calcination ☞ Sintering ☞ Coating Application

Type	Dimension(mm) (W×L×H)	Temperature Range ($^{\circ}\text{C}$)
EF-01	500×500×500	100~1200
EF-02	800×800×800	100~1200
EF-03	1000×1000×1000	100~1200
EF-04	1500×1500×1500	100~1200
EF-05	2000×2000×2000	100~1200
EF-C	Customized upon request	100~1200